



THERMAL RATINGS DATA

Series Model	Test Number	Glazing Configuration	U-Value	SHGC	VT
Contemporary Series Casement Window	NCTL-110-19572-1E0A0	LowE366/Arg/Clear 3mm	0.25	0.18	0.41
		LowE270/Arg/Clear 3mm	0.26	0.21	0.44
		LowE366/Arg/Clear/Arg/Clear 3mm	0.21	0.16	0.37
		12mm Lam/Arg/3mm/LowE366	0.30	0.23	0.38
Contemporary Series Awning Window	NCTL-110-19571-1E0A0	LowE366/Arg/Clear 3mm	0.26	0.17	0.40
		LowE270/Arg/Clear 3mm	0.27	0.23	0.44
		LowE366/Arg/Clear/Arg/Clear 3mm	0.22	0.16	0.37
		12mm Lam/Arg/3mm/LowE366	0.30	0.11	0.37
Contemporary Series Fixed Window	NCTL-110-19571	LowE366/Arg/Clear 3mm	0.27	0.22	0.52
		LowE270/Arg/Clear 3mm	0.27	0.30	0.57
		LowE366/Arg/Clear/Arg/Clear 3mm	0.20	0.21	0.48
		12mm Lam/Arg/3mm/LowE366	0.31	0.30	0.49